

**NORTHERN GREECE CERAMICS S.A.**

Nea Santa 61100 - Kilkis, Greece

Tel: 0030 23410 75570

Fax: 0030 23410 75574

Email: info@kebe-sa.gr

web: www.kebe-sa.gr

EST. 1935

**KOTHALI****KEBE**

NORTHERN GREECE CERAMICS

**20****EN 771-1:2011+A1:2015****ORTHOBLOCK K 120****Vertically Perforated Clay Masonry unit P, for use in protected masonry,  
Category II**

DOP Reference No	K120-20B	
Length	380	mm
Width	120	mm
Height	240	mm
Dimensional tolerance	T1	
Range category	R1	
Flatness of bed faces	≤1	mm
Plane parallelism of bed faces	≤1	mm
Configuration	As in attached drawing	
Gross dry density	850	kg/m <sup>3</sup>
Net dry density	1900	kg/m <sup>3</sup>
Density tolerance	D1:10	%
Mean compressive strength (perpendicular to bed face)	≥7,5	N/mm <sup>2</sup>
Category	II	
Bond strength (Tabulated value acc.to EN 998-2 Annex C)	0,30	N/mm <sup>2</sup>
Thermal conductivity λ <sub>10,dry,unit</sub> (P3)	0,2172	W/mK
Water vapour permeability μ	5/10	
Durability against freeze/thaw	F0	
Water absorption	NPD	
Active soluble salt content	S0	
Reaction to fire : Euroclass	A1	
Dangerous substances	NPD	

**Particular conditions applicable to the use:**

Cutting with power tools may generate dust. People undertaking works of this nature are advised to wear suitable personal protective equipment (PPE)



# Declaration of Performance

No: K120-20B

Unique identification code of the product-type : ORTHOBLOCK K120

Intended Use/es: Protected masonry structures

Manufacturer: NORTHERN GREECE CERAMICS S.A.

Nea Santa, 61100 - Kilkis, Greece  
Tel: 0030 23410 75570  
Fax: 0030 23410 75574  
Email: info@kebe-sa.gr  
web: www.kebe-sa.gr



System/s AVCP : System 4

Harmonised standard: EN 771-1:2011+A1:2015

## Declared performance/s:

Essential characteristics	Performance		Harmonized technical specification
Length	380	mm	EN 772-16
Width	120	mm	EN 772-16
Height	240	mm	EN 772-16
Dimensional tolerance	T1		EN 771-1
Range category	R1		EN 771-1
Flatness of bed faces	≤1	mm	EN 772-20
Plane parallelism of bed faces	≤1	mm	EN 772-16
Gross Dry density	850	kg/m <sup>3</sup>	EN 772-13
Net dry density	1900	kg/m <sup>3</sup>	EN 772-13
Density tolerance	D1:10	%	EN 771-1
Mean compressive strength (perpendicular to bed face)	≥7,5	N/mm <sup>2</sup>	EN 772-1
Category	II		EN 771-1
Bond strength (Tabulated value according to EN 998-2 Annex C)	0,30	N/mm <sup>2</sup>	EN 998-2
Thermal conductivity $\lambda_{10,dry,unit}$ (P3)	0,2172	W/mK	EN 1745
Water vapour permeability $\mu$	5/10		EN 1745
Durability against freeze/thaw	F0		EN 771-1
Water absorption	NPD		EN 771-1
Active soluble salt content - category	S0		EN 771-1
Reaction to fire - Euroclass	A1		EN 771-1
Dangerous substances	NPD		EN 771-1

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

George Koutsoupas - Quality Systems Manager

Nea Santa 11/05/2020

