

**NORTHERN GREECE CERAMICS S.A.**

Nea Santa 61100 - Kilkis, Greece

Tel: 0030 23410 75570

Fax: 0030 23410 75574

Email: info@kebe-sa.gr

web: www.kebe-sa.gr

EST. 1935

**KOTHALI****KEBE**

NORTHERN GREECE CERAMICS

**16****EN 771-1:2011+A1:2015****No 60****Horizontally Perforated Clay Masonry unit P, for use in protected masonry,  
Category II**

DOP Reference No	N60-19A	
Length	250	mm
Width	60	mm
Height	120	mm
Dimensional tolerance	T1	
Range category	R1	
Flatness of bed faces	NPD	
Plane parallelism of bed faces	NPD	
Configuration	As in attached drawing	
Gross dry density	880	kg/m <sup>3</sup>
Net dry density	1832	kg/m <sup>3</sup>
Density tolerance	D1:10	%
Mean compressive strength (perpendicular to bed face)	≥3,0	N/mm <sup>2</sup>
Category	II	
Bond strength (Tabulated value acc.to EN 998-2 Annex C)	0,15	N/mm <sup>2</sup>
Thermal conductivity $\lambda_{10,dry,unit}$ (P3)	NPD	
Water vapour permeability $\mu$	5/10	
Durability against freeze/thaw	F0	
Water absorption	NPD	
Active soluble salt content	S0	
Reaction to fire : Euroclass	A1	
Dangerous substances	NPD	

**Particular conditions applicable to the use:**

Cutting with power tools may generate dust. People undertaking works of this nature are advised to wear suitable personal protective equipment (PPE)



# Declaration of Performance

No: N60-19A

Unique identification code of the product-type : No 60

Intended Use/es: Protected masonry structures

Manufacturer: NORTHERN GREECE CERAMICS S.A.

Nea Santa, 61100 - Kilkis, Greece  
Tel: 0030 23410 75570  
Fax: 0030 23410 75574  
Email: info@kebe-sa.gr  
web: www.kebe-sa.gr



System/s AVCP : System 4

Harmonised standard: EN 771-1:2011+A1:2015

## Declared performance/s:

Essential characteristics	Performance		Harmonized technical specification
Length	250	mm	EN 772-16
Width	60	mm	EN 772-16
Height	120	mm	EN 772-16
Dimensional tolerance	T1		EN 771-1
Range category	R1		EN 771-1
Flatness of bed faces	NPD		EN 771-1
Plane parallelism of bed faces	NPD		EN 771-1
Gross Dry density	880	kg/m <sup>3</sup>	EN 772-13
Net dry density	1832	kg/m <sup>3</sup>	EN 772-13
Density tolerance	D1:10	%	EN 771-1
Mean compressive strength (perpendicular to bed face)	≥3	N/mm <sup>2</sup>	EN 772-1
Category	II		EN 771-1
Bond strength (Tabulated value according to EN 998-2 Annex C)	0,15	N/mm <sup>2</sup>	EN 998-2
Thermal conductivity $\lambda_{10,dry,unit}$ (P3)	NPD		EN 1745
Water vapour permeability $\mu$	5/10		EN 1745
Durability against freeze/thaw	F0		EN 771-1
Water absorption	NPD		EN 771-1
Active soluble salt content - category	S0		EN 771-1
Reaction to fire - Euroclass	A1		EN 771-1
Dangerous substances	NPD		EN 771-1

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

George Koutsoupas - Quality Systems Manager

Nea Santa 17/12/2019

